





QY25K-II Total lifting load for primary boom						
Fully extended outrigger without the 5th outrigger, boom at the side or the rear or with the 5th outrigger at 360 degrees swing						
Working radius (m)	Basic boom 10.70m	Half boom 15.36m	Half boom 20.02m	Half boom 24.68m	Half boom 29.34m	Fully boom 34.00m
	Lifting load (kg)	Lifting load (kg)	Lifting load (kg)	Lifting load (kg)	Lifting load (kg)	Lifting load (kg)
3.0	25000					
3.5	25000	18000				
4.0	24000	18000	16000			
4.5	22200	17500	16000	11000		
5.0	20200	17500	16000	10900		
5.5	18200	17500	15200	10600	8000	
6.0	16500	16600	14300	10400	8000	
6.5	15000	15300	13200	10000	8000	7100
7.0	13300	13700	12500	9500	8000	7000
8.0	10600	11000	11000	8800	7500	6700
9.0		9000	9300	8200	7100	6200
10.0		7500	7800	7500	6500	5700
12.0		6300	5600	5900	5600	4600
14.0			4200	4500	4500	4100
16.0			3200	3500	3600	3700
18.0				2800	2800	2800
20.0				2300	2300	2300
22.0				1800	1800	1900
24.0					1500	1500
26.0					1100	1200
28.0						900
30.0						700
Parts of line	10	7	6	4	3	3
Angle area	32° ~ 69°	32° ~ 74°	32° ~ 77°	21° ~ 79°	24° ~ 79°	25° ~ 79°
Weight of hook block	250kg					